## **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **LISTING OF CLAIMS:**

1 - 7. (Canceled)

8. (Currently Amended) A tube connecting apparatus which connects flexible tubes to each other, comprising:

a holding unit having a placement clamp section at which the tube is placed, a movable clamp section which is movable in a direction of pressing the tube which is placed at the placement clamp section and in a direction of separating from the tube, and a hook section which is set up at the movable clamp section and which engages the placement clamp section to maintain a pressing state of the movable clamp section against the tube;

a cutting unit which cuts the tubes held in a flat state by the holding unit; and a movement unit which moves the holding unit to change relatively positions of the tubes cut by the cutting unit such that end portions to be connected face each other,

wherein the holding unit has a plurality of divided hook portions at the hook section in a direction orthogonal to a longitudinal direction of the tube placed at the placement clamp section, and wherein at least one of the hook portions is made of an elastic member which maintains engagement with the placement clamp section,

Attorney Docket No. 1012774-000005 Application No. 10/562,829

Page 3

the elastic member having a protruded portion at one side which protrudes relative to

other hook portions and having an other side fixed to the hook section,

wherein the holding unit has a first holding section and a second holding

section which are disposed along a longitudinal direction of the tubes placed at the

placement clamp section, and

wherein the first holding section has a shaft which protrudes from an end face

disposed at a side of the second holding section of the movable clamp section, and

the second holding section has a long hole formed at a side of the first holding

section of the movable clamp section and into which the shaft is inserted.

9. (Previously Presented) A tube connecting apparatus according to claim 8,

wherein the cutting unit cuts the tubes between the first holding section and the

second holding section.

10. (Original) A tube connecting apparatus according to claim 9, wherein the

movement unit moves at least one of the first holding section and the second holding

section in a direction of the longitudinal direction of the tubes placed at the

placement clamp section and in a direction orthogonal to the tubes.

11. (Original) A tube connecting apparatus according to claim 10, wherein

the elastic member is made of resin having a flexure property of bending so as to

change its self-shape according to external pressure.

Attorney Docket No. 1012774-000005 Application No. 10/562,829

Page 4

12. (Original) A tube connecting apparatus according to claim 11, wherein

the elastic member is disposed at a center of the hook portions which are provided

parallel, and wherein a material of the other hook portions is made of metal.

13. (Previously Presented) A tube connecting apparatus according to claim

8, wherein the elastic member is disposed at a center of the hook portions which are

provided parallel, and wherein a material of the other hook portions is made of metal.

14. (Previously Presented) A tube connecting apparatus according to claim

8. wherein the placement clamp section has an engagement member which engages

the protruded portion of the elastic member, and wherein a material of the

engagement member is made of resin.

15. (Previously Presented) A tube connecting apparatus according to claim

14, wherein the engagement member is a rotatable roller, and wherein the protruded

portion of the elastic member slides to contact a circumferential surface of the roller

to be located to an engagement maintaining position at which the protruded portion

maintains engagement with the roller.

16. (New) A tube connecting apparatus according to claim 8, wherein the

shaft and the long hole, when engaged, allow movement of the holding unit by the

movement unit to change relatively the positions of the tubes.